

Knauf Fill & Finish

Data Sheet



Knauf Fill & Finish is an easy-to-sand jointing compound for bedding tapes and finishing joints in drywall partitions and ceilings. Ready-mixed for quick and easy application.

Knauf Application

Knauf Fill & Finish is a ready-mixed, all purpose finishing compound, suitable for use as a joint finish as well as for full surface levelling. Knauf Fill & Finish is for internal use only and can be used on the following substrates:

- Gypsum boards
- Gypsum fibre boards
- Concrete/aerated concrete
- Plaster
- Precision block masonry

Physical Characteristics

Tub Size	Packaging unit/pallet	Material No
Kg		
20	33	601443

Storage and Handling

Protect against frost, high temperatures and exposure to direct sunlight. Can be stored for up to 12 months at room temperature.

Compliance

Bedding and finishing compound type 3A acc. to EN 13963:2014.

Performance Data

In compliance with EN 13963:2014, the product is subject to initial type testing and continuous factory production control and bears the CE mark.

Technical Data

Reaction to fire:
Class A2-s1,d0 acc. to EN 13963:2014

Product Features

- Ready-mixed
- No mixing or setting times
- Pliable consistency
- Easy application
- Very easy to sand
- Good adhesive properties

Application/Installation

Substrate

Remove any existing release agents, e.g. wallpaper paste or paper residue. The gypsum board must be dry, clean and dust free and should be firmly fastened to the substructure.

For masonry background, pre-fill large cracks and damaged areas with Knauf Uniflott. Pre-filled areas must be dry and be well adjusted to the plasterboard surface.

Mixing

Stir compound properly, add a little water to make consistency leaner if necessary. Use clean mixing buckets / tools.

Machines and equipment

Tools: Trowel, wide spatula.

Jointing of gypsum boards

Fill joints and screw heads, apply tape and embed with a trowel. Before applying the next layer, the previous layer must be fully dry.

Drying time

Application time will vary depending on ambient temperature and air humidity.

Application temperature/climate

The material, substrate and air temperature during application and until fully dry should not fall below +10°C.

Notes

Do not mix Knauf Fill & Finish with other materials. Clean tools with water after use. Depending on room temperature and air humidity, expect longer drying times for thicker layers.

Coverage

Estimating guide: 45m² per 20kg tub

Coatings and linings

Pretreat and prime surfaces before the application of coatings and linings (wallpapers) in accordance with BS 8212:1995 Section 6.7.

Related Products

Knauf Fill & Finish should be used in conjunction with the following products:

Knauf Joint Tape
Material No. 258337



Knauf Fibre Tape
Material No. 493679



Health & Safety

Refer to the product MSDS and also the Knauf Guidance for Safe Material Management document:

MSDS:
<http://www.knauf.co.uk/product-data-sheets>

Safe Material Management:
<http://www.knauf.co.uk/literature>

Sustainability Credentials:
Please view Product Sustainability Credentials Sheet:
<http://www.knauf.co.uk/product-data-sheets>

Customer Service

UK Tel: 0800 521 050
Eire Tel.: 01 4620739
Email: orders@knauf.co.uk

Technical Service

UK Tel.: 0800 030 4135
Eire Tel.: 01 4620739
E-mail: technical@knauf.co.uk

Literature

UK Tel: 03700 613 700
Eire Tel.: +44 3700 613 700

Website

www.knauf.co.uk
www.knauf.ie

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Knauf
87 Broomhill Road
Tallaght
Dublin 24



KNAUF