DOP

## GYPROC PLASTERBOARD

**Declaration of Performance** 

Unique identification code of the product-type:

Gyproc Plasterboards

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Gyproc WallBoard: 9.5mm, 12.5mm, 15mm

Gyproc SoundBloc: 12.5mm, 15mm Gyproc FireLine: 12.5mm, 15mm Gyproc DuraLine: 13.5mm, 15mm

Gyproc Moisture Resistant WallBoard: 12.5mm, 15mm Gyproc Moisture Resistant Fireline: 12.5mm, 15mm

Cyproc WallPoard Promium: 12 Emm

Gyproc WallBoard Premium : 12.5mm

Gyproc CoreBoard : 19mm Gyproc Plank : 19mm

Gyproc WallBoard 4x2s: 9.5mm, 12.5mm

Gyproc WallBoard 8x2s: 12.5mm

Gyproc WallBoard 900mm wide :12.5mm

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Plasterboard lining

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Saint-Gobain Construction Products (Irl) Limited Unit 4 Kilcarbery Business Park,

Nangor Road, Dublin 22.

Tel: +353 (0)1 629 8400

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4 generally System 3 for Reaction to Fire

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The Building Test Centre, Notified body No. 1575 issued reports relating to System 3 classification requirements for reaction to fire

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A





## 9 Declared performance :

The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification
Shear strength	NPD	N/A
Reaction to fire	A2-s1, d0	EN 13501 - 1
Water vapour resistance factor	10	EN 12524
Flexural strength	Conforms	EN 520 : 2004 + A1:2009
Impact resistance	Performance declared is for the system of which the product is a part. Refer to Gyproc literature	
Direct airborne sound insulation		
Acoustic absorption		
Thermal conductivity	0.25 W/mk	EN 12524

## The performance of the products identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Saint-Gobain Construction Products (Irl) Limited Kilcarbery Office 21/08/17

**Freephone ROI:** 1800 744480

Freephone NI: 0845 3990159

Email: tech.ie@saint-gobain.com

www.gyproc.ie

Gyproc, Gypframe and Glasroc are all registered trade names of Saint-Gobain Construction Products (Irl) Limited. Isover is a registered trade name of Saint-Gobain.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up-to-date library of information visit the Gyproc website at: www.gyproc.ie





