



Product Name Vario Bond

A High Performance Airtight Plasterable Junction Tape For Windows, Doors and Timber to Block Connections, for use with our VARIO membranes as part of our VARIO Airtightness and Moisture management system

Part of the Vario range



Vario Bond



BENEFITS AND FEATURES

MULTI-APPLICATION	Internal & external use
PLASTERABLE	Can be plastered or rendered over with Gypsum based undercoat plasters, sand and cement and exterior renders
STRENGTH	High adhesive strength – bonds to variety of substrates
HIGH PERFORMANCE	Airtight, windtight and driving rain proof
EASY TO INSTALL	Pre-split, with finger-lift function for easy installation

STANDARDS & CERTIFICATION

QUALITY	We hold a Quality Management Standard BS EN ISO 9001: 2008 for manufacturing.
CE	All products are manufactured in accordance with the CE marking requirements under the Construction Products Regulation,
PRODUCT STANDARDS	All our products are manufactured in accordance with product standard: BS EN 13162: 2008 and BS EN 13172 Evaluation of Conformity.
ENVIRONMENT	ISOVER is an ISO 14001:2004 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system. EN ISO 13162 EMS 551706 003 BS EN ISO 9001: 2000
INDOOR AIR QUALITY	Vario Bond has been certified for indoor air quality and holds the GEV Emission EC1+.

For more applications and product details, please visit www.isover.ie



Vario Bond Applications



Timber wall plate to block junction



Window junctions



Floor to wall junctions

JUNCTIONS

- ✓ Timber wall plate
- ✓ Internal Windows
- ✓ External Windows
- ✓ Internal Floors

SUBSTRATES

- ✓ Vario Membrane
- ✓ Timber
- ✓ PVC
- ✓ Concrete Block
- ✓ Metal & Concrete Lintels
- ✓ PVC Cavity Closers

Basic Installation Steps



1. Prepare and install any corner details for wall, window or floor corner sections, before you begin further application.



6. Use roller to firmly ensure good adhesion to background.



2. For ceiling to wall connections, cut the Vario membrane with a 15mm lip down the wall.




7. Repeat the above installation steps for both window detailing and floor to wall detailing. Refer to our full installation guide for application specifics.



3. Apply 15mm edge strip from Vario Bond to Vario membrane.



4. Remove centre strip from Vario Bond and apply to background.



5. Remove end strip from Vario Bond and apply to background.



8. Once tape has been applied to all connections, proceed with plastering with Gypsum based plaster or Sand & Cement



ISOVER Ireland
Unit 4, Kilcarbery Business Park,
Nangor Rd., Dublin 22
Tel: +353 (0) 1 629 8400
Email: info@isover.ie
Web: www.isover.ie

ISOVER Technical Team
ROI Free Phone: 1800 744 480
NI Phone: 0845 399 0159
Email: tech.ie@saint-gobain.com