



Product Name

VARIO KM Duplex UV

Used as a vapour retarder and airtight barrier in ventilated and nonventilated roofs and walls, in conjunction with suitable adhesive tape, sealing tape, sealant and joint sealing strip.

Part of the Vario range



VARIO KM Duplex UV



BENEFITS AND FEATURES


MATERIAL	Modified fabric-reinforced polyamide faced with a special polypropylene fabric.
FIRE	Euroclass E (normally flammable) in accordance with DIN 13984.
MOISTURE	Vapour permeable breathable insulation. Improves energy performance and reduces heating & cooling costs.
STRENGTH	≥ 110 N/50 mm in accordance with EN 13984.
TEMPERATURE	(- 40°C to + 80°C.)
WATER VAPOUR DIFFUSION	Approx. 109.7 g/m ² d to 6.6 g/m ² d in accordance with EN 12572.

STANDARDS & CERTIFICATION

QUALITY	We hold a Quality Management Standard BS EN ISO 9001: 2008 for manufacturing.
CE	All products are manufactured in accordance with the CE marking requirements under the Construction Products Regulation,
PRODUCT STANDARDS	All our products are manufactured in accordance with product standard: BS EN 13162: 2008 and BS EN 13172 Evaluation of Conformity.
ENVIRONMENT	ISOVER is an ISO 14001:2004 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system. EN ISO 13162 EMS 551706 003 BS EN ISO 9001: 2000



VARIO KM Duplex UV Application



Masonry

Dry Lining

Single Brick Construction

- 1 215 mm brick
- 2 13mm Gyproc Plaster
- 3 Optima metal studs + fixings
- 4 ISOVER insulation
- 5 VarioKM Duplex + Vario adhesive tape
- 6 Gyproc WallBoard

For more applications and product details, please visit www.isover.ie

ISOVER Ireland
Unit 4, Kilcarbery Business Park,
Nangor Rd., Dublin 22
Tel: +353 (0) 1 629 8400
Email: info@isover.ie
Web: www.isover.ie

ISOVER Technical Team
ROI Free Phone: 1800 744 480
NI Phone: 0845 399 0159
Email: tech.ie@saint-gobain.com

